



Aluminium Scaffold Towers Ltd.

☎ 01353 778811

✉ sales@aluminium-scaffoldtowers.co.uk

🌐 www.aluminium-scaffoldtowers.co.uk

850 Mobile Aluminium Scaffold Tower Tested and Certified to EN 1004-1:2020



Type Approved
Safety
Regular Production
Surveillance
www.tuv.com
ID: 1111247258

Tower Dimension : 0.85m(W) x 2.5m(L) x 11.2m(H)
Max. Platform Height : 10.2m, Max. Working Height : 12.2m

Maximum Working Load :
Tower - 950 kg including tower self weight
Platform - 275 kg when load uniformly distributed

Item	Description	Qty.
1.	Castor Wheel 150mm dia. W/Adj. Leg	4
2.	850 2 Rung Ladder Frame 0.85m x 1.0m	1
3.	850 2 Rung Span Frame 0.85m x 1.0m	1
4.	850 3 Rung Ladder Frame 0.85m x 1.5m	-
5.	850 3 Rung Span Frame 0.85m x 1.5m	-
6.	850 4 Rung Ladder Frame 0.85m x 2.0m	5
7.	850 4 Rung Span Frame 0.85m x 2.0m	5
8.	Trapdoor Platform 0.6m x 2.5m	3
9.	Horizontal Brace 2500 (Red)	14
10.	Diagonal Brace 2700 (Blue)	19
11.	Folding Toeboard 0.6m x 2.5m	1
12.	Fixed Outrigger - Small	-
13.	Telescopic Outrigger - Medium	4
14.	Telescopic Outrigger - Large	-
Scale : NTS Ref. : SW-11200-25		
Weight : approx. 259.0kg		

