



Aluminium Scaffold Towers Ltd.

01353 778811

sales@aluminium-scaffoldtowers.co.uk

www.aluminium-scaffoldtowers.co.uk

850 Mobile Aluminium Scaffold Tower Tested and Certified to EN 1004-1:2020



Tower Dimension : 0.85m(W) x 1.8m(L) x 9.7m(H)
Max. Platform Height : 8.7m, Max. Working Height : 10.7m

Maximum Working Load :
Tower - 950 kg including tower self weight
Platform - 275 kg when load uniformly distributed

Item	Description	Qty.
1.	Castor Wheel 150mm dia. W/Adj. Leg	4
2.	850 2 Rung Ladder Frame 0.85m x 1.0m	-
3.	850 2 Rung Span Frame 0.85m x 1.0m	-
4.	850 3 Rung Ladder Frame 0.85m x 1.5m	1
5.	850 3 Rung Span Frame 0.85m x 1.5m	1
6.	850 4 Rung Ladder Frame 0.85m x 2.0m	4
7.	850 4 Rung Span Frame 0.85m x 2.0m	4
8.	Trapdoor Platform 0.6m x 1.8m	3
9.	Horizontal Brace 1800 (Red)	14
10.	Diagonal Brace 2100 (Blue)	16
11.	Folding Toeboard 0.6m x 1.8m	1
12.	Fixed Outrigger - Small	-
13.	Telescopic Outrigger - Medium	4
14.	Telescopic Outrigger - Large	-
Scale : NTS		Ref. : SW-9700-18
Weight : approx. 214.3kg		

