

**LOYAL**

SAFE WORKING

# Aluminium Scaffold Towers Ltd.

01353 778811

sales@aluminium-scaffoldtowers.co.uk

www.aluminium-scaffoldtowers.co.uk

## Trade King 730

Tested &amp; Certified to EN 1004-1:2020

Type Approved Safety Regular Production Surveillance  
www.tuv.com ID: 1113297296Tower Dimension : 0.73m(W) x 1.55m(L) x 7.77m(H)  
Max. Platform Height : 6.6m, Max. Working Height : 8.6mSafety Working Load :  
Platform - 230 kg when load uniformly distributed

Item	Description	Qty.
1.	Fixed Castor Wheel Ø125mm	4
2.	4 Rung Frame 0.73 x 1.0m	-
3.	6 Rung Folded Base Frame Unit	1
4.	8 Rung Frame 0.73 x 2.0m	6
5.	Trapdoor Platform 0.6 x 1.55m	3
6.	Horizontal Brace 1.55m	13
7.	Diagonal Brace 1.7m	11
8.	Wooden Toeboard Set 0.6 x 1.55m	1
9.	Fixed Outrigger	-
10.	Telescopic Outrigger	4

Scale : NTS

Ref. : TKG005F855

Weight : approx. 141.5kg

